

LineaPro 7

| | |
|--------------------------------------|--|
| Microcontroller | Cortex-M3 |
| Buttons | 2 scan buttons, 1 battery status button, 1 reset device button |
| Magnetic Card Reader | Triple track bi-directional Encryption head (optional) |
| Contactless Reader (optional) | ISO/IEC 14443 Type A MIFARE Mini, MIFARE Classic 1K, MIFARE Classic 4K, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Plus 2K, MIFARE Plus 4K, MIFARE DESFire ISO/IEC 14443 Type B ISO/IEC 15693 JIS X 6319-4 - FeliCa ISO/IEC 18000-3 - NFC |
| 1D Barcode Reader | Opticon MDL-1000 Laser Scan Engine (optional) |
| 2D Barcode Reader | Newland EM3096 / 3396 - 752 x 480 CMOS (optional) Newland EM3296 - 640 x 480 CMOS (optional) Opticon MDI-4000 - 640 x 480 CMOS (optional) Honeywell N6600 SR - 844 x 640 CMOS (optional) Honeywell N6600 MR - 844 x 640 CMOS (optional) Zebra SE4710 - 1280 x 800 CMOS (optional) Zebra SE4750 SR - 1280 x 960 CMOS (optional) Zebra SE4750 MR - 1280 x 960 CMOS (optional) |
| Connectors | USB Type-C port Lightning connector (cradle) Power transfer to phone |
| Wired Communication | RS-232, USB (pass-through sync) |
| Bluetooth (optional) | BT version 2.0 power class 2 |
| Device Compatibility | iPhone 8, iPhone 7, iPhone 6, iPhone 6s |
| LED Indication | Battery status |
| Audio Features | Electromagnetic buzzer |
| Power Supply | DC 5 V through USB, DC 5 V through contact pins |
| Battery | Rechargeable Li-Ion Battery 3.6 V, 2400 mAh, Fuel Gauge |
| Reliability | 1,000,000 magnetic card swipes |
| Certificates | CE, PCI PTS 3.x, Apple Mfi |
| Dimension W x D x H | 77 x 157 x 27 mm |
| Weight | 148 g |
| Operational Temperature | -10 °C to 40 °C / 5 to 90% RH |
| Storage Temperature | -20 °C to 50 °C / 5 to 90% RH |
| Drop Tested | 1.5 m, faces and edges |
| Box Contents | LineaPro 7 device, 90 cm USB Type-A to Type-C cable |
| Compatible Accessories | Charger (GT1), 5-unit charger (GT5), Dual charger, Holster, Multi Battery Charger (MBC5) |

